



Enclosure Power Supply

Enclosure Power Supply 开放式恒压电源

Features 特性

- Constant voltage design
- ETL/cETL, CE, ROHS approval
- AC input power suitable for the world
- High efficiency and low operation temperature
- Wattage : 15W-600W
- With short-circuit and overload protection
- Compact size, light weight
- 100% full-load burn-in test
- Installed with EMI filter, minimum wave
- 2 years warranty

产品特性：恒压设计

产品认证：ETL/cETL、CE、ROHS认证

输入电压：国际通用全范围输入电压

产品优势：性能稳定，使用寿命长

功率：15w-600w

保护功能：过流/过载/短路保护，过温保护功能

外观：体积小，重量轻

满载老化测试率：100%

线路设计：EMI过滤

质保期：两年

Application 适用范围

- LED lighting box, LED Module and LED strips etc
- LED Neon
- LED urban Decoration
- LED Lighting Advertising
- LED Display
- Safety Protection Apparatus
- Telecommunications
- Networks

LED模组、灯条、灯箱

LED霓虹灯

LED城市装饰灯

LED广告灯

LED 显示屏

安全防护装置

通信装置

网络装置

Model 型号	Cover Material 外壳材质	Input Voltage 输入电压 (Vac)	Output Voltage 输出电压 (VDC)	Output Current 输出电流 (Amp)	Output Power 输出功率 (Watt)	Product Size 尺寸 (mm)	N / W 净重 (g)
SMT-012-015SA	Aluminium(IP20)	AC100-240v	12	1.25	15	78*48*22	75
SMT-024-015SA	Aluminium(IP20)	AC100-240v	24	0.62	15	78*48*22	75
SMT-012-025SA	Aluminium(IP20)	AC100-240v	12	2.08	25	85*58*38	165
SMT-024-025SA	Aluminium(IP20)	AC100-240v	24	1.04	25	85*58*38	165
SMT-012-036SA	Aluminium(IP20)	AC100-240v	12	3.00	36	85*58*38	165
SMT-024-036SA	Aluminium(IP20)	AC100-240v	24	1.50	36	85*58*38	165
SMT-012-048SA	Aluminium(IP20)	AC100-240v	12	4.00	48	112*88*34	400
SMT-024-048SA	Aluminium(IP20)	AC100-240v	24	2.00	48	112*88*34	400
SMT-012-060SA	Aluminium(IP20)	AC100-240v	12	5.00	60	112*88*34	500
SMT-024-060SA	Aluminium(IP20)	AC100-240v	24	2.50	60	112*88*34	500
SMT-012-072SA	Aluminium(IP20)	AC100-240v	12	6.00	72	112*88*34	500
SMT-024-072SA	Aluminium(IP20)	AC100-240v	24	3.00	72	112*88*34	500
SMT-012-096SA	Aluminium(IP20)	AC100-240v	12	8.00	96	160*88*34	650
SMT-024-096SA	Aluminium(IP20)	AC100-240v	24	4.00	96	160*88*34	650
SMT-012-120SA	Aluminium(IP20)	AC100-240v	12	10.0	120	160*88*34	650
SMT-024-120SA	Aluminium(IP20)	AC100-240v	24	5.00	120	160*88*34	650
SMT-012-150SA	Aluminium(IP20)	AC100-240v	12	12.5	150	199*110*50	720
SMT-024-150SA	Aluminium(IP20)	AC100-240v	24	6.25	150	199*110*50	720
SMT-012-200SA	Aluminium(IP20)	AC100-240v	12	16.7	200	199*110*50	900
SMT-024-200SA	Aluminium(IP20)	AC100-240v	24	8.33	200	199*110*50	900
SMT-012-250SA	Aluminium(IP20)	AC100-240v	12	20.8	250	199*110*50	900
SMT-024-250SA	Aluminium(IP20)	AC100-240v	24	10.4	250	199*110*50	900
SMT-012-320SA	Aluminium(IP20)	AC100-240v	12	26.7	320	215*115*50	1000
SMT-024-320SA	Aluminium(IP20)	AC100-240v	24	13.3	320	215*115*50	1000
SMT-012-350SA	Aluminium(IP20)	AC100-240v	12	29.1	350	215*115*50	1000
SMT-024-350SA	Aluminium(IP20)	AC100-240v	24	14.6	350	215*115*50	1000
SMT-012-400SA	Aluminium(IP20)	AC100-240v	12	33.3	400	215*115*50	1000
SMT-024-400SA	Aluminium(IP20)	AC100-240v	24	16.7	400	215*115*50	1000
SMT-012-500SA	Aluminium(IP20)	AC100-240v	12	41.7	500	235*124*65	1250
SMT-024-500SA	Aluminium(IP20)	AC100-240v	24	20.8	500	235*124*65	1250
SMT-012-600SA	Aluminium(IP20)	AC100-240v	12	50.0	600	235*124*65	1250
SMT-024-600SA	Aluminium(IP20)	AC100-240v	24	25.0	600	235*124*65	1250

Product Display

产品展示

