



Constant Voltage

Constant Voltage LED Drivers

普通恒压电压(防水)

Features

特性

- Constant voltage design
- Working mode : constant voltage type
- ETL/cETL,CE, ROHS approval
- Input voltage : 100-265v (< 100w),
90-135v/170-265v (> 100w)
- High efficiency and low operation temperature
- Wattage : 12W-300W
- Efficiency : >83%
- With short-circuit and overload protection
- Compact size, light weight
- 100% full-load burn-in test
- Installed with EMI filter, minimum wave
- 2 years warranty

产品特性：恒压设计

工作模式：恒压模式

产品认证：ETL/cETL、CE、ROHS认证

输入电压：100-265v (小于100w)

90-135v/170-265 (>100w)

产品优势：性能稳定，使用寿命长

功率：12w-300w

性能：>83%

保护功能：过流/过载/短路保护，过温保护功能

外观：体积小，重量轻

满载老化测试率：100%

线路设计：EMI过滤

质保期：两年

Application

适用范围

- Indoor & outdoor LED illuminating lights.
- LED Neon,
- LED City Decoration
- LED Lighting Advertising,
- LED Display, Strips, Light bar
- Commercial LED Lighting,
- LED Panels

户内外LED照明灯光

LED霓虹灯

LED城市装饰灯

LED广告灯带

LED显示屏，灯带，灯条

商用LED照明

LED面板灯

Model 型号	Cover Material 外壳材质	Input Voltage 输入电压 (Vac)	Output Voltage 输出电压 (VDC)	Output Current 输出电流 (Amp)	Output Power 输出功率 (Watt)	Product Size 尺寸 (mm)	N / W 净重 (g)
SMT-012-012VW	Aluminum(IP67)	AC100-265v	12	0.10	12	66*29*20	91
SMT-024-012VW	Aluminum (IP67)	AC100-265v	24	0.50	12	66*29*20	91
SMT-012-018VW	Plastic/Aluminum	AC100-265v	12	1.50	18	116*44*20(IP20)	108
SMT-024-018VW	Plastic/Aluminum	AC100-265v	24	0.75	18	130*29*20(IP67)	108
SMT-012-024VW	Plastic/Aluminum	AC100-265v	12	2.00	24	140*45*28(IP20)	118
SMT-024-024VW	Plastic/Aluminum	AC100-265v	24	1.00	24	182*29*20(IP67)	118
SMT-012-030VW	Plastic/Aluminum	AC100-265v	12	2.50	30	140*45*28(IP20)	118
SMT-024-030VW	Plastic/Aluminum	AC100-265v	24	1.25	30	182*29*20(IP67)	118
SMT-012-036VW	Plastic/Aluminum	AC100-265v	12	3.00	36	140*45*28(IP20)	118
SMT-024-036VW	Plastic/Aluminum	AC100-265v	24	1.50	36	217*29*21(IP67)	118
SMT-012-040VW	Aluminum(IP67)	AC100-130v	12	3.33	40	217*29*21	205
SMT-024-040VW	Aluminum (IP67)	AC170-265v	24	1.67	40	217*29*21	205
SMT-012-048VW	Aluminum(IP67)	AC100-265v	12	4.00	48	220*40*22	300
SMT-024-048VW	Aluminum (IP67)	AC100-265v	24	2.00	48	220*40*22	300
SMT-012-060VW	Aluminum(IP67)	AC100-265v	12	5.00	60	190*48*34	550
SMT-024-060VW	Aluminum (IP67)	AC100-265v	24	2.50	60	190*48*34	550
SMT-012-072VW	Aluminum(IP67)	AC100-265v	12	6.00	72	190*48*34	550
SMT-024-072VW	Aluminum (IP67)	AC100-265v	24	3.00	72	190*48*34	550
SMT-012-096VW	Aluminum(IP67)	AC100-265v	12	8.00	96	200*68*53	900
SMT-024-096VW	Aluminum (IP67)	AC100-265v	24	4.00	96	200*68*53	900
SMT-012-120VW	Aluminum(IP67)	AC90-135v	12	10.0	120	242*68*53	1100
SMT-024-120VW	Aluminum (IP67)	AC170-265v	24	5.00	120	242*68*53	1100
SMT-012-150VW	Aluminum(IP67)	AC90-135v	12	12.5	150	240*71*45	1250
SMT-024-150VW	Aluminum (IP67)	AC170-265v	24	6.25	150	240*71*45	1250
SMT-012-200VW	Aluminum(IP67)	AC100-265v	12	16.7	200	240*96*43	1300
SMT-024-200VW	Aluminum (IP67)	AC100-265v	24	8.33	200	240*96*43	1300
SMT-012-250VW	Aluminum(IP67)	AC90-135v	12	20.8	250	235*120*56	2540
SMT-024-250VW	Aluminum (IP67)	AC170-265v	24	10.4	250	235*120*56	2540
SMT-012-300VW	Aluminum(IP67)	AC170-265v	12	25.0	300	235*120*56	2400
SMT-024-300VW	Aluminum (IP67)	AC170-265v	24	12.5	300	235*120*56	2400

Product Display

产品展示

